



Catalog Number	Finish	Lamp	Wattage	Color Temp	Voltage
DMS01	Clear with Etched Face	LED	1W	3000K	120-240V

## Features

- Heat Sink/Driver Housing:** Die cast aluminum.
- Lens:** Injection molded acrylic sandblasted with clear polished edges, developed for optimum optical output.
- Acrylic Mounting Plate:** Die cast aluminum.
- Re-modeler Junction Box:** Die cut and formed 16ga. Galvanized steel. Can be used in new or existing construction.

## Electrical

**LED:** (1) 1W 3000K white LED. Average expected life, under normal operating conditions is 50,000 hours with lumen maintenance of 70% of original light output.

**Driver:** Integral Class 2 power supply.

**Voltage:** 120V

**Output Wattage:** 1 W

**Input Current (max.):** 65 mA

**Frequency:** 50/60 Hz

**Output Voltage (VDC):** 4 V

**Constant Current:** 350 mA

## Finish

Lens – Sandblasted acrylic with clear polished edges.

## Labels

cULus Listed. Suitable for Dry Locations. Type IC.

Wall mount only.

## Job Information

## Type:

**Job Name:**

**Cat. No.:**

**Lamp(s):**

**Notes:**

631 Airport Road, Fall River, MA 02720 • (508) 679-8131 • Fax (508) 674-4710

We reserve the right to change details of design, materials and finish.

www.lightolier.com © 2008 Philips Group • B1208